

Catalogue number	LED qty/ W	High Power LED Chip/ LED Driver	Colour Temperature	Brightness WW/PW/CW	Beam angle	Power Factor	Input Voltage	Cable length	IP Grade
FL-10-WW/PW/CW	1*10	BRIDGELUX 45mil.	WARM WHITE 2800-3500K	1100/1150/1200	120°	>0,95	AC85-265V	2m	IP65
FL-20-WW/PW/CW	1*20	BRIDGELUX 45mil.		2200/2300/2400	120°	>0,95	AC85-265V	2m	IP65
FL-30-WW/PW/CW	1*30	BRIDGELUX 45mil.		3300/3450/3600	120°	>95%	AC85-265V	2m	IP65
FL-50-WW/PW/CW	1*50	BRIDGELUX 45mil.		5500/5750/6000	120°	>95%	AC85-265V	2m	IP65
FL-70-WW/PW/CW	1*70	BRIDGELUX 45mil.		7700/8050/8400	120°	>95%	AC85-265V	2m	IP65
FL-80-WW/PW/CW	2*40	BRIDGELUX 45mil./ Meanwell	PURE WHITE 5000-5500K	9600/10000/10400	120°	>0,95	AC85-265V	2m	IP65
FL-100-WW/PW/CW	2*50	BRIDGELUX 45mil./ Meanwell		12000/12500/13000	120°	>0,95	AC85-265V	2m	IP65
FL-120-WW/PW/CW	2*60	BRIDGELUX 45mil./ Meanwell	COOL WHITE 6500-7000K	14400/15000/15600	120°	>0,95	AC85-265V	2m	IP65
FL-140-WW/PW/CW	2*70	BRIDGELUX 45mil./ Meanwell		16800/17500/18200	120°	>0,95	AC85-265V	2m	IP65
FL-160-WW/PW/CW	4*40	BRIDGELUX 45mil./ Meanwell		19200/20000/20800	120°	>0,95	AC85-265V	2m	IP65
FL-200-WW/PW/CW	4*50	BRIDGELUX 45mil. Meanwell		24000/25000/26000	120°	>95%	AC85-265V	2m	IP65

LED FLOOD LIGHT can be ordered with a motion sensor(PIR). Please write PIR at the end of the part number, eg. FL-20-PW-PIR.

