



Catalogue number	LED PANEL	Dimensions/mm	Lumens Flux/lm WW/NW/CW	Picture
<b>7PAN145 WW/NW/CW</b>	CIRCLE 7W	145	500/600/550	
<b>10PAN180 WW/NW/CW</b>	CIRCLE 10W	180	800/900/950	
<b>12PAN200 WW/NW/CW</b>	CIRCLE 12W	200	1000/1100/1050	
<b>15PAN220 WW/NW/CW</b>	CIRCLE 15W	220	1200/1300/1250	
<b>15PAN240 WW/NW/CW</b>	CIRCLE 15W	240	1200/1300/1250	
<b>18PAN300 WW/NW/CW</b>	CIRCLE 18W	300	1600/1700/1650	
<b>48PAN600 WW/NW/CW</b>	CIRCLE 48W	600	4300/4700/4500	

<b>12PAN2020 WW/NW/CW</b>	SQUARE 12W	200x200	1000/1100/1050	
<b>12PAN3030 WW/NW/CW</b>	SQUARE 12W	300x300	1000/1100/1050	
<b>18PAN3030 WW/NW/PW</b>	SQUARE 18W	300x300	1600/1700/1650	
<b>30PAN6060 WW/NW/CW</b>	SQUARE 30W	600x600	2800/2900/2850	
<b>36PAN6060 WW/NW/CW</b>	SQUARE 36W	600x600	3400/3500/3450	
<b>40PAN6060 WW/NW/CW</b>	SQUARE 40W	600x600	3800/3900/3850	
<b>48PAN6060 WW/NW/CW</b>	SQUARE 48W	600x600	4600/4700/4650	
<b>60PAN6060 WW/NW/CW</b>	SQUARE 60W	600x600	5800/5900/5850	
<b>40PAN6262 WW/NW/CW</b>	SQUARE 40W	620x620	3800/3900/3850	
<b>48PAN6262 WW/NW/CW</b>	SQUARE 48W	620x620	4600/4700/4650	

<b>18PAN3060 WW/NW/CW</b>	RECTANGLE 18W	300x600	1600/1700/1650	
<b>25PAN3060 WW/NW/CW</b>	RECTANGLE 25W	300x600	2300/2400/2350	
<b>30PAN3060 WW/NW/CW</b>	RECTANGLE 30W	300x600	2800/2900/2850	
<b>20PAN15120 WW/NW/CW</b>	RECTANGLE 20W	150x1200	1700/1800/1850	
<b>40PAN30120 WW/NW/CW</b>	RECTANGLE 40W	300x1200	3800/3900/3850	
<b>48PAN30120 WW/NW/CW</b>	RECTANGLE 48W	300x1200	4600/4700/4650	
<b>60PAN30120 WW/NW/CW</b>	RECTANGLE 60W	300x1200	5700/5900/5800	
<b>48PAN30150 WW/NW/CW</b>	RECTANGLE 48W	300x1500	4500/4600/4550	
<b>60PAN60120 WW/NW/CW</b>	RECTANGLE 60W	600x1200	5200/5300/5250	
<b>70PAN60120 WW/NW/CW</b>	RECTANGLE 70W	600x1200	6700/6800/6750	


**Colour temperature: WARM WHITE 2800-3500K, NEUTRAL WHITE 4000-4500K, COOL WHITE 6000-6500K**

Input Voltage: AC85-265V / Output Voltage: DC30-40V


Power Factor: 0,95 / Thickness: 12,5mm

IP: 41 / Warranty: 2 years


Distribution Curve of Meridian






LED Panel 36W 600x600mm  
Illumination Cone Curve





Conical Intensity Distribution Curve of Max Intensity



Catalogue number	LED PANEL	Dimensions/mm	Lumens Flux/Im WW/NW/CW	Picture
<b>40PANW3080 WW/NW/CW</b>	RECTANGLE 40W	300x800	3800/3900/3850	
<b>48PANW3080 WW/NW/CW</b>	RECTANGLE 48W	300x800	4600/4700/4650	
<b>48PANW30120 WW/NW/CW</b>	RECTANGLE 48W	300x1200	4600/4700/4650	
<b>60PANW30120 WW/NW/CW</b>	RECTANGLE 60W	300x1200	5800/5900/5850	

<b>PANR20X20S</b>	FRAME SILVER	200x200		
<b>PANR30X30S</b>	FRAME SILVER	300x300		
<b>PANR60X30S</b>	FRAME SILVER	600x300		
<b>PANR60X60S</b>	FRAME SILVER	600x600		
<b>PANR62X62S</b>	FRAME SILVER	620x620		
<b>PANR120X30S</b>	FRAME SILVER	1200x300		
<b>PANR120X60S</b>	FRAME SILVER	1200x600		

The CEILING FRAMES can be ordered in other colors, eg. white, gold (additional cost).

<b>PANL300</b>	HANGER WIRE for	300		
<b>PANL600</b>	HANGER WIRE for	600		
<b>PANMB300</b>	MOUNTING BRACKET	300		
<b>PANMB600</b>	MOUNTING BRACKET	600		

**Colour temperature: WARM WHITE 2800-3500K, NEUTRAL WHITE 4000-4500K, COOL WHITE 6000-6500K**

Input Voltage: AC85-265V / Output Voltage: DC30-40V

Power Factor: 0,95 / IP: 41

Warranty: 2 years

