







Catalogue number	Lumens Flux/Module	Size (mm)	LEDs	Picture	Modules Net Spacing(mm)	Beam angle	Modules/ String	Power (W)
<b>LM201</b>	cool white 38 lm	48×15×4,5	<b>2 pcs 5050 SMD</b>		65	120°	max. 20 pcs	0.48W
<b>LM501</b>	cool white 16 lm	39×12×4,5	<b>3 pcs 3528 SMD</b>		40	120°	max. 20 pcs	0.3W
<b>LM301 LM304 LM305 LM306 LM307</b>	cool white 55 lm blue 10,5 lm red 10,5 lm green 18 lm yellow 10,5 lm	78×15×4,5	<b>3 pcs 5050 SMD</b>		85	120°	max. 20 pcs	0.72W
<b>LM401</b>	cool white 74 lm	36×36×4,5	<b>4 pcs 5050 SMD</b>		83	120°	max. 20 pcs	0.96W
<b>LM308</b>	RGB (red 3 lm blue 9,6 lm green 2,4 lm)	78x15x4,5	<b>3 pcs 5050 SMD</b>		85	120°	max. 20 pcs	0.72W
<b>LML301 LML303</b> (constant current, warranty 3 years)	warm white cool white exposed Aluminium PCB for better heat dissipation, ABS injection overmolded, with 90% transmittance lens 120 lm	80x15x6,8	<b>3pcs 5630 SMD</b>		85	160°	max. 20 pcs	1,2W

Voltage: DC12V / IP Grade: IP65  
 Efficiency: >95% / Colour rendering index: Ra>85  
 Working temperature: -20°C +60°C / Certification: CE,RoHS  
 Warranty: 2 years